

Piezoresistive silicon pressure transmitter
 St. steel body for industrial application
 with Declaration of conformity, CE

DAHO
 2024.03.08



Model: EDN.320, Flush diaphragm
 Sensor type: Piezo_resistive silicon sensor
 Accuracy: $\leq \pm 0.5\%$
 Wetted parts: all st. steel
 Application: air, oil, water as well as aggesive media



| Pressure Transmitter | Model | 기본판매가격(원) |
|----------------------|-------|-----------|
|----------------------|-------|-----------|

| | | |
|--------|---------|---------|
| Model: | EDN.320 | 337,000 |
|--------|---------|---------|

| Scope | Code | Specifications | 선택사양 추가금액(원) |
|-------|------|----------------|--------------|
|-------|------|----------------|--------------|

| | | | |
|-----------------------|----|-------------------------|---|
| Analog output signals | O1 | 4...20mA, 2-wire system | - |
| | O2 | 0...10V, 3-wire system | - |
| | O3 | 0...5V, 3-wire system | - |
| | O4 | 1...5V, 3-wire system | - |

| | | | |
|-----------------------|---|-------------|--------|
| Electrical connection | D | DIN 43650 A | - |
| | M | M12 plug | 20,500 |
| | C | 2m Cable | 7,000 |

| | | | |
|---------------------|----|----------------------------------|---|
| Pressure connection | G2 | G 1/2" (PF 1/2") Flush diaphragm | - |
|---------------------|----|----------------------------------|---|

| | | | |
|-----------------------|---------|---------|---|
| Pressure Ranges / bar | R19 | -1...0 | - |
| | R23 | 0...1 | - |
| | R26 | 0...1.6 | - |
| | R28 | 0...2.5 | - |
| | R30 | 0...4 | - |
| | R32 | 0...6 | - |
| | R33 | 0...10 | - |
| | R35 | 0...16 | - |
| | R37 | 0...25 | - |
| | R39 | 0...40 | - |
| | R41 | 0...60 | - |
| | R43 | 0...100 | - |
| | R45 | 0...160 | - |
| R47 | 0...250 | - | |

[선택사양]

| | | | |
|-----------------------|----|---------------|--------|
| Operating temperature | T4 | -40...+125 °C | 60,000 |
|-----------------------|----|---------------|--------|

| | | | |
|-------------|-----|------------------------------------|---------|
| Accessories | CD2 | Cooling device up to 200 °C | 250,000 |
| | CD3 | Cooling device up to 300 °C | 300,000 |
| | TP | St steel tag plate, 60 x 20 x 0.5t | 9,500 |

| | | | |
|--------------|-----|-------------------------------|-------|
| Cable length | 2MC | 2m cable standard | 5,000 |
| | ACM | additional extension cable /m | 2,000 |

| | | | |
|--------------|------|-------------------------------------|--------------------|
| Certificates | DMCC | DAHO manufacturing calibration card | price included |
| | KC | KOLAS calibration certificate | KOLAS 교정가격표를 참조하세요 |