



Model MBXC.3xx (incl. Glycerine)

Dial size: 63mm

Element type bourdon tube < 60 bar & helical tube ≥ 60 bar

Accuracy Class 1.6% per EN 837-1

Wetted parts: Cooper alloy

Specification	Code			Unit price(원)
Model:	MBX	:	For hydraulic & pneumatic application	
Basic Unit price based	on origin			Unit prices on each model
중국OEM제품	MBXC. 311	:	Bottom connection	16,800
5   52    <u>1</u>	MBXC. 321	:	Bottom connecton with 3-hole back flange	19,900
	MBXC. 331	:	Back connection	20,700
	MBXC. 341	:	Back connection with 3-hole front flange	23,900
Options				Additional prices
Liquid filling	0	:	Dry	-
3	1	:	Glycerin	
Pressure connection	G4	:	G1/4" (PF1/4")	
	R4	:	R1/4" (PT 1/4")	-
	XX	:	Others	Refer to options
Unit of measurement	В	:	bar	-
ornic or mododromoric	K	:	kPa	-
	M	:	MPa	-
	P	:	psi	-
	D	:	dual scale (MPa-inner & bar-outer)	-
	Χ	•	others	Refer to options
Pressure Ranges / bar	R19	:	-10	1,000
· ·	R23	:	01	
	R26	:	01.6	
	R28	:	02.5	
	R30	:	04	
	R32	:	06	no extra charge
	R33	:	010	no extra charge
	R35	:	016	
	R37	:	025	
	R39	:	040	
	R40	:	050 only for bottom connection	
	R41	:	060	
	R43	:	0100	
	R45	:	0160	no extra charge
	R47	:	0250	
	R50	:	0400	
	R53	<u>:</u>	0600	10
	R55	:	01000 only for bottom connection	12,500

## **Options**

1	. On dial face				
		OR	:	Other pressure range per pcs	15,000
		ND	:	New dial face design / new scale	120,000
		GM	:	Green marking per pcs	4,300
		CD	:	New dial face design with company logo	80,000
2	2. Accessories				
		RS	:	Restricter screw in socket hole for high pulsation	3,000
		UC	:	U-clamp for back connection, steel	14,300
		NO	:	Washing for application "USE NO OIL" per pcs, at least ≥ 10 pcs	3,800

	SG	:	Safety glass	3,000
	FF	:	Front flange with 3-hole, stainless steel	4,000
	BF	:	Back flange with 3-hole, stainless steel	4,000
	TP	:	St steel tag plate, 60 x 20 x 0.5t	10,000
3. Certificates				
	DMCC	:	Manufature calibration certificate	8,000
	KC	:	KOLAS / ilac-MRA calibration certificate	refer to KOLAS list price