

Bourdon tube pressure gauge
Pressure gauge with turret case series MAP
St. steel material & thermoplastic case



Model	MAP
Element type	bourdon tube
Accuracy	Grade 0.5% per ASME B40.100
Wetted parts:	St.steel
Application:	measuring gaseous, liquid and aggressive media

Specification	Code	Currency (원)
Standard Price	MAP6 / 125mm	189,000
Additional Prices		
Type of mounting	1 : Bottom connection	-
	3 : Back connection	64,200
Liquid filling	0 : Dry	-
	1 : Glycerin	19,200
Pressure connection	N2 : NPT1/2"	-
	XX : Others	<i>on request</i>
Unit of measurement	B : bar	-
	K : kPa	-
	M : MPa	-
	P : psi	-
	D : dual scale (MPa-inner & bar-outer)	-
	X : others	<i>on request</i>
Pressure Ranges / bar	R23 : 0...1	<i>no extra charges</i>
	R26 : 0...1.6	
	R28 : 0...2.5	
	R30 : 0...4	
	R32 : 0...6	
	R33 : 0...10	
	R35 : 0...16	
	R37 : 0...25	
	R39 : 0...40	
	R41 : 0...60	45,000
	R43 : 0...100	
	R45 : 0...160	
	R47 : 0...250	
	R50 : 0...400	
	R53 : 0...600	
R55 : 0...1000	162,000	

Options

1. On dial face	OR	: Other pressure range per pcs	14,300
	ND	: New dial face design	114,300
	NF	: New dial face printing cost per pcs	4,300
	GM	: Green marking per pcs	4,300
	CD	: New dial face design with company logo	72,000
2. Accessories	RS	: Restrictor screw in socket hole for high pulsation	2,300
	UC	: U-clamp for back connection, steel	14,300
	NO	: Washing for application "USE NO OIL" per pcs, at least ≥ 10 pcs	3,800
	SG	: Safety glass	2,900
	TP	: St steel tag plate, 60 x 20 x 0.5t	9,000
3. Certificates	MC	: Manufature calibration certificate	8,000
	KC	: KOLAS / ilac-MRA calibration certificate	refer to KOLAS list price