

Piezoresistive silicon pressure transmitter
 St. steel body for industrial application
 with Declaration of conformity, CE

DAHOJ

2024.02.05



Model	EDN.331
Sensor type	Piezo_resistive silicon sensor
Accuracy	≤ ±0.5%
Wetted parts:	all st. steel
Electrical connection:	General head for outdoor applications

Pressure Transmitter	Model	Currency (EUR)
----------------------	-------	----------------

Model:	EDN.331	<i>Basic price</i>	157.08
---------------	---------	--------------------	--------

Scope	Code	Specifications	Additional Prices
-------	------	----------------	-------------------

Analog output signals	O1	4...20mA, 2-wire system	-
	O2	0...10V, 3-wire system	-
	O3	0...5V, 3-wire system	-
	O4	1...5V, 3-wire system	-

Electrical connection	H	General head, similar to thermocouple head	<i>included</i>
-----------------------	---	--	-----------------

Pressure connection	R4	R 1/4" (PT 1/4")	-
	G4	G 1/4" (PF 1/4")	-
	R38	R 3/8" (PT 3/8")	-
	G2	G 1/2" (PF 1/2")	-
	XX	Others	<i>additional costs</i>

Pressure Ranges / bar	R19	-1...0	<i>no extra charges</i>
	R23	0...1	
	R26	0...1.6	
	R28	0...2.5	
	R30	0...4	
	R32	0...6	
	R33	0...10	
	R35	0...16	
	R37	0...25	
	R39	0...40	
	R41	0...60	
	R43	0...100	
	R45	0...160	
	R47	0...250	
	R50	0...400	
	R53	0...600	
R55	0...1000		

Options available

1. Accuracy	A5	±0.5% F.S	<i>included</i>
	A6	±0.3% F.S	80.77
	A7	±0.15% F.S	134.62
2. Accessories	TP	St steel tag plate, 60 x 20 x 0.5t	15.77
3. Cable length	2MC	2m Standard, additional 1m	1.54
4. Certificates	DMCC	Manufaturer's calibration certificate	6.15
	KC	KOLAS calibration certificate	<i>refer to KOLAS list price</i>