

Piezoresistive silicon pressure transmitter for low pressure measurement  
 All st. steel body for industrial application  
 with Declaration of conformity, CE

**DAHO**

2024.02.05



Model: EDN.324  
 Sensor type: Piezo\_resistive silicon sensor  
 Accuracy: ≤ 1.0% FS ≤250 mbar, >0.5% FS > 250 mbar  
 Wetted parts: all st. steel  
 Application: Air and gases measurement application / HVAC

Pressure Transmitter	Model	Currency (EUR)
----------------------	-------	----------------

Model:	EDN.324	Basic price	235.54
--------	---------	-------------	--------

Scope	Code	Specifications	Additional Prices
-------	------	----------------	-------------------

Analog output signals	O1	: 4...20mA, 2-wire system	-
	O2	: 0...10V, 3-wire system	-
	O3	: 0...5V, 3-wire system	-
	O4	: 1...5V, 3-wire system	-

Electrical connection	D	: DIN 43650 A	-
	M	: M12 plug	15.77
	C	: 2m Cable	3.85

Pressure connection	G4	: G1/4" (PF1/4")	-
	R4	: R1/4" (PT1/4")	-
	G2	: G1/2" (PF1/2")	-
	XX	: Others	on request

Pressure Ranges / mbar	R126	: 0...25 mbar	no extra charges
	R128	: 0...40 mbar	
	R130	: 0...60 mbar	
	R131	: 0...100 mbar	
	R133	: 0...160 mbar	
	R135	: 0...250 mbar	
	R137	: 0...400 mbar	
	R21	: 0...600 mbar	
	R23	: 0...1000 mbar	

**Options**

1. Accessories	CD2	: Cooling device up to 200 °C	192.31
	CD3	: Cooling device up to 300 °C	230.77
	TP	: St steel tag plate, 60 x 20 x 0.5t	7.31
2. Cable length		2m Standard, additional 1m	1.54
3. Certificates	DMCC	: DAHO manufacturing calibration card	6.15
	KC	: KOLAS calibration certificate	refer to KOLAS list price