

Piezoresistive silicon pressure transmitter
 St. steel body for industrial application
 with Declaration of conformity, CE

DAHO
 2024.02.05



Model	EDN.301
Sensor type	Piezo_resistive silicon sensor
Accuracy	≤ 0.15%
Wetted parts:	all st. steel
Application:	air, oil, water as well as aggesive media

Pressure Transmitter	Model	기본 판매가격(원)
----------------------	-------	------------

Model:	EDN.301	<i>Basic price</i> 510,300
--------	---------	----------------------------

Scope	Code	Specifications	선택사항 추가금액(원)
-------	------	----------------	--------------

Analog output signals	O1	4...20mA, 2-wire system	-
	O2	0...10V, 3-wire system	-
	O3	0...5V, 3-wire system	-
	O4	1...5V, 3-wire system	-

Electrical connection	D	DIN 43650 A	-
	M	M12 plug	20,500
	C	2m Cable	5,000

Pressure connection	G2	G 1/2" (PF 1/2")	-
	G3	G 3/8" (PF 3/8")	-
	G4	G 1/4" (PF 1/4")	-
	R2	R 1/2" (BSPT 1/2")	-
	R3	R 3/8" (BSPT 3/8")	-
	R4	R 1/4" (BSPT 1/4")	-
	XX	Others	<i>추가금액 발생</i>

Pressure Ranges / bar	R19	-1...0	-
	R23	0...1	-
	R26	0...1.6	-
	R28	0...2.5	-
	R30	0...4	-
	R32	0...6	-
	R33	0...10	-
	R35	0...16	-
	R37	0...25	-
	R39	0...40	-
	R41	0...60	-
	R43	0...100	-
	R45	0...160	-
	R47	0...250	-
	R50	0...400	-
	R53	0...600	-
R55	0...1000	-	

[선택사항]		
----------	--	--

Operating temperature	T4 : -40...+125 °C	60,000
-----------------------	--------------------	--------

Accessories	CD2	Cooling device up to 200 °C	250,000
	CD3	Cooling device up to 300 °C	300,000
	TP	St steel tag plate, 60 x 20 x 0.5t	9,500

Cable length	2MC	2m cable standard	5,000
	ACM	additional extension cable /m	2,000

Certificates	DMCC	DAHO manufacturing calibration card	price included
	KC	KOLAS calibration certificate	KOLAS 교정비용 참조하세요