



| | |
|-------------|-------------------------------|
| Model | ODi-5G |
| Sensor type | Piezoresistive silicon sensor |
| Accuracy | Accuracy 0.4% FS |
| Wetted part | 304SS |
| Application | Gas or liquid |

| Specification | Code | Currency (EUR) |
|----------------------|-----------------------|--------------------------------------------|
| | | <i>Standard Price</i> |
| Model: | ODi-5G : 100 mm | 176.15 |
| | | <i>[QPDR: Group "A"] Additional Prices</i> |
| Pressure Connection | G2 : PF 1/2" | - |
| | N2 : NPT 1/2" | on request |
| Pressure Range / bar | R23 : -1...0 | |
| | R106 : -50...50 mbar | 20.77 |
| | R08 : -1...10 bar | |
| | R23 : 0...1 | |
| | R130 : 0...60 mbar | |
| | R131 : 0...100 mbar | |
| | R135 : 0...250 mbar | |
| | R28 : 0...2.5 | |
| | R30 : 0...4 | |
| | R32 : 0...6 | |
| | R33 : 0...10 | |
| | R35 : 0...16 | No extra costs |
| | R37 : 0...25 | |
| | R39 : 0...40 / stock | |
| | R41 : 0...60 | |
| | R43 : 0...100 / stock | |
| | R45 : 0...160 | |
| | R47 : 0...250 / stock | |
| | R50 : 0...400 / stock | |
| | R53 : 0...600 / stock | |
| | R55 : 0...1000 | 80.00 |

Option

| | | |
|--------------|------------------------------------|---------------------------|
| Accessories | CD2 : Cooling device up to 200 °C | 153.85 |
| | CD3 : Cooling device up to 300 °C | 176.15 |
| | A42 : G1/4(F) x G1/2(M) | 134.62 |
| | A4M : G1/4(F) x M20x1.5(M) | 134.62 |
| Certificates | DMCC: DAHO function test report | 6.15 |
| | KC : KOLAS calibration certificate | Refer to KOLAS List Price |