

Piezoresistive silicon pressure transmitter for scrubber application
St. steel body for industrial application
with Declaration of conformity, CE

DAHOJ

2020. 03. 18



Model	EDS.315
Sensor type	Piezoresistive silicon sensor
Accuracy	≤ 0.5%
Wetted parts:	all st. steel
Application:	air, oil, water as well as aggesive media

Specification	Code	Currency (원)
Model:	EDS.315	<i>Standard Price</i> 214,300
		<i>Additional Prices</i>
Analog output signals	O1 : 4...20mA, 2-wire system	-
	O2 : 0...10V, 3-wire system	-
	O4 : 0.5...4.5V analog output	-
	O5 : 1...5V	-
	O6 : 0.5...4.5V, ratio-metric	<i>not available</i>
	Electrical connection	D : DIN 43650 A
M : M12 plug		-
B : Binder plug		<i>not available</i>
C : 2m Cable		4,300
Pressure connection	G4 : G1/4"(PF1/4") with 6mm hole	-
	R4 : R1/4"(PT1/4") with 6mm hole	-
	G2 : G1/2"(PF1/2") with 10mm hole	-
	XX : Others	<i>on request</i>
Pressure Ranges / mbar	R105 : ± 25 mbar	<i>no extra charges</i>
	R106 : ± 50 mbar	
	R119 : ± 250 mbar	
	R122 : ± 500 mbar	

Options

1. Accessories	CD2 : Cooling device up to 200℃	200,000
	CD3 : Cooling device up to 300℃	229,000
	TP : St steel tag plate, 60 x 20 x 0.5t	9,000
2. Cable length	2m Standard, additional 1m	900
	3. Certificates	
	MC : Manufature standard calibration report	8,000
	KC : KOLAS calibration certificate	refer to KOLAS list price